

**Rental Solutions** 

**180k Zone 2 Nitrogen Pump** 

## **CE Marked**

This globally recognised 180k nitrogen pump from Prior Power Solutions is designed and manufactured to a high standard with ease of operation and ongoing maintenance at the core.

Our nitrogen pumping unit can also be operated at 15,000 psi working pressure by utilising a simple conversion kit, giving greater flexibility on operational parameters.



Design features	
Area classification	ATEX Zone 2
Design	DNV 2.7-1 Offshore certified skid
Maximum flow rate	180,000 SCFH
Maximum working pressure	10,000 psi or 15,000 psi
GN2 Discharge temperature	c21°C



**Reliable Equipment** 



24/7 Support



**Easy Operation** 

### **POWER SOLUTIONS FOR A CHANGING WORLD**

# 180k Zone 2 Nitrogen Pump

**CE Marked** 





Pump specification	
Make/model	ICPE 200
Max input pressure	240 HP
Cold end	1.625"
Maximum working pressure	10,000 psi
Maximum flow	3,000 SCFM

Unit dimensions/weight	
Length	5,080 mm
Width	2,438 mm
Height	2,670 mm
Weight	13,000 kg





#### Safety features

- Engine overspeed
- · High exhaust gas temperature
- High engine coolant temperature
- · Low engine lube oil pressure
- · Low hydraulic oil level
- · Spark arrestor silencer
- Emergency stop button

#### **Applications for use**

- Purging
- · Well fracturing
- · Nitrified fluid injection
- · Coiled tubing
- Well bore cleanouts
- Nitrified fluids
- Nitrogen perforation
- · Pipeline and process applications

#### **Options**

- 15,000 psi conversion kit
- · Comprehensive OEM-training
- · Temperature shutdown skid
- · Over pressurisation skid
- Critical maintenance pack
- · Data acquisition system
- Operator canopy

# Contact us today.

For all well intervention equipment, rental, sale and maintenance.